



Type Designation	4006
Designation IEC	LR6
System	Zn-MnO ₂ (Alkaline)
Shelf Life (Coding)*	10 years
Nominal Voltage [V]	1.5
Typical Capacity C [mAh]	2970 (discharge with high-resistance)
Permissible Temperature Range	- 20 °C ... 50 °C
Weight, approx. [g]	23,8
Volume [ccm]	7.5

Dimensions [mm] min: max:

∅	13.7	14.5
A	-	50.5
B	49.5	-
C	7.0	-
E	-	0.5
F	-	5.5
G	1.0	-

Typical Capacities (at 20°C):



Discharge Type	Load	End Voltage[V]	1.0
1H /8H/D,7D/W Radio / Clock / Remote Control	50 mA	Time [h]	52,3
		Capacity [Ah]	2,63
		Energy [Wh]	3,40
Discharge Type	Load	End Voltage[V]	0.9
1H/D,7D/W Toy, non motorized	250 mA	Time [h]	9,0
		Capacity [Ah]	2,2
		Energy [Wh]	2,7
Discharge Type	Load	End Voltage[V]	0.9
4M/H, 8H/D, 7D/W Portable Lighting	3,9 Ω	Time [min]	468
		Capacity [Ah]	2,38
		Energy [Wh]	2,86

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries

* In consideration of typical loss of capacity at storage and application.