

PA-L19.R006



Dimensions

Length	67	± 2 mm
Width	18.5	± 1 mm
Height	22	± 1 mm

Data for Pack

Nominal voltage		3.6V	2.5V - 4.2V		
Nominal capacity		2250mAh	typical		
Used cell in pack		1pcs	Panasonic UR18650A		
Internal resistance pack		185mΩ	±10%		
Max charge voltage		4,2V			
Charge current	standard	430mA	10°C < T < 45°C		
	rapid	1500mA	10°C < T < 45°C		
Discharge	standard	430mA	-20°C < T < 60°C *below 0°C with limited performance		
	max. cont.	2200mA	-20°C < T < 60°C *below 0°C with limited performance		
	max. peak	2950mA	-20°C < T < 45°C t < 1ms *below 0°C with limited performance		
Short circuit current		≥22A	> 500μs		
NTC		10kΩ	technical Data NTC		
Connector	JST	XHP-3	Pin1	GND	black
			Pin2	NTC	yellow
			Pin3	PLUS	red
Cable Length		45 mm	± 5 mm		
Weight		ca. 45g	± 5 g		
Watt-hour rating		7.8Wh	acc. to UN38.3 Certificate		

Limitations by Safety Unit (SU) @ Ta 25°C

over voltage (per cell)	cut off	4275mV	± 25mV
	release	4075mV	± 25mV
under voltage (per cell)	cut off	2300mV	± 0,050 V
	release	3V	± 0,050 V
Current Limit 1 by SU		≤2.2A	continous
Current Limit 2 by SU		≥2.95A	>2,24 ms
short circuit protection		≤20A	>320μs typical
Power consumption	active	< 12.5μA	@4.2V ±5μA
	shutdown	< 1.5μA	-0/+1μA (when Ubat < 2.25V)
ESD Protection		NO	

Recommended Charger

1 Cell CC/CV Charger